



RCF3 - Roofing Compliance Form for Tile Roof Cover – New Roof or Re-Roof

All sections must be completed and signed by installing Roofing Contractor Responsible Party to confirm that roof products and installation meet FORTIFIED Roof requirements. Form not valid if all sections are not filled out, initialed and/or signed by Roofing Contractor. Location and date stamped photos documenting roof installation must match RCF to achieve FORTIFIED designation.

General Information (complete a thru h):

- a. FORTIFIED ID: _____ (Obtain from homeowner or FORTIFIED Evaluator)
b. Homeowner's Name: _____
c. Property Street Address: _____
d. City: _____
e. State: _____
f. ZIP: _____
g. County: _____
h. Date of roof installation: _____

1. Permit information (complete a, b, c, d, OR e):

- a. Permit Number: _____
b. Dated: _____
c. Issued by the _____ (County/City/State) Building Department
d. Date of final inspection by Building Department _____
e. _____ Initial here if no permit was issued

2. Site Conditions (complete a thru f):

- a. Building Code and Edition: _____
b. Design Wind Speed (minimum Vult = 130 mph): _____
c. Exposure Category: B [] C [] D []
d. Lowest slope of all roof areas with tile roof cover: ____/12

NOTE: If there are multiple roof cover types on the same home, separate Roofing Compliance Forms must be submitted for each roof cover type.

- e. Mean Roof Height (MRH): _____ ft
MRH = 1/2 (height from ground to eave + height from ground to ridge)
f. [] Check here if site is within 3,000 ft of saltwater

NOTE: if site is within 3,000 ft of saltwater, fasteners and connectors must comply with FORTIFIED Corrosion Protection Requirements per Standard Detail F-G-1

3. Required Design Uplift Pressures (complete a):

- a. Enter required ASD design uplift pressures corresponding to no less than Vult = 130 mph and Exposure C for the MRH and roof slope entered above.

(For identification of Roof Zones, refer to FORTIFIED Standard Detail F-G-2 "Roof and Wall Zone Diagram").

Zone 1: _____ psf Zone 2: _____ psf Zone 3: _____ psf

If different design pressures have been utilized for different areas of the roof, note them below:

Area's MRH ____ Area's slope ____; Zone 1: _____ psf Zone 2: _____ psf Zone 3: _____ psf
Area's MRH ____ Area's slope ____; Zone 1: _____ psf Zone 2: _____ psf Zone 3: _____ psf



RCF3 - Roofing Compliance Form for Tile Roof Cover – New Roof or Re-Roof

4. Roof Sheathing (Decking) Type and Thickness (complete a thru d):

- a. Sheathing type: **MINIMUM 15/32"** Plywood/OSB **MINIMUM 3/4"** Wood board
Other _____ (Check One/Write In)
- b. Sheathing thickness: _____
- c. Check here to confirm that sheathing thickness meets minimum FORTIFIED requirements per section 4.1 of FORTIFIED Home 2020 Standard
- d. Check here if sheathing does NOT meet minimum FORTIFIED thickness requirements, and professional engineer has provided signed and sealed letter verifying sheathing is adequately rated for span, applicable design wind pressures, and dead load from tile weight.

5. Roof Sheathing Attachment (complete a OR b):

- a. New Roof Sheathing:
 - i. If wood board sheathing, enter nail type used and number of nails per board installed into each roof member intersection:

 Check here to confirm that wood board sheathing attachments meets FORTIFIED requirements per Standard Detail [F-RS-1](#) "Roof Deck Attachment - Sawn Lumber or Wood Board Roof Deck with No Gaps"
 - ii. If plywood/OSB sheathing, enter nail type used and installed nail spacing:

Check here to confirm that plywood/OSB sheathing attachment meets FORTIFIED requirements per one of the following Standard Details (check the one that applies):

- [F-RS-2](#) "Hurricane - New Construction Roof Deck Attachment - Structural Wood Panels" for Hurricane Designation
- [F-RS-3](#) "High Wind - New Construction Roof Deck Attachment - Structural Wood Panels" for High Wind Designation

b. Re-Roof (Using Existing Sheathing):

- i. Enter nail type used and installed additional nail spacing:

Check here to confirm that existing sheathing has been re-nailed to meet FORTIFIED requirements per one of the following Standard Details (check the one that applies):

- [F-RR-3](#) "Hurricane - Re-Nailing the Roof Deck (Wood Structural Panels)" for plywood/OSB for Hurricane Designation
- [F-RR-4](#) "High Wind - Re-Nailing the Roof Deck (Wood Structural Panels)" for plywood/OSB for High Wind Designation
- Existing wood board sheathing has been re-nailed to meet the requirements of [F-RS-1](#) "Roof Deck Attachment - Sawn Lumber or Wood Board Roof Deck with No Gaps"

6. Sealed Roof Deck: (complete a)

- a. For tile roof covers, check here to confirm that roof deck has been sealed per one of the following methods illustrated in the FORTIFIED Standard Details (check the one(s) that apply):
 - [F-SRD-5](#) "Sealed Roof Deck - Flashing Tape, Underlayment and Roof Tile Cap Sheet - Concrete and Clay Tile Roof Covers, Steep Slope"
 - [F-SRD-6](#) "Sealed Roof Deck - Self-Adhered Membrane - Concrete and Clay Tile Roof Covers, Steep Slope"



RCF3 - Roofing Compliance Form for Tile Roof Cover – New Roof or Re-Roof

7. Drip Edge: (complete a thru c)

- a. Is Installed drip edge (edge flashing) code compliant material? Yes No
- b. Was NEW drip edge (edge flashing) installed? Yes No
- c. Check here to confirm that drip edge is installed per one of the following methods (check the one that applies):
 - [F-DE-1](#) "Hurricane - Drip Edge Installation Over Underlayment" for Hurricane designation
 - [F-DE-3](#) "High Wind - Drip Edge Installation Over Underlayment" for High Wind designation
 - Other: Drip edge installed per manufacturer specifications

8. Flashing: (complete a thru c)

- a. Is Installed flashing code compliant material? Yes No
- b. Was NEW flashing installed? Yes No
- c. Check here to confirm that new, corrosion-resistant flashing and fasteners in accordance with FORTIFIED Standard Detail [F-G-1](#) "Corrosion Protection Requirements" have been installed at all roof interruptions and terminations per manufacturer specifications as described in section 4.6 of FORTIFIED Home 2020 Standard.

9. Clay and Tile Roof Covering (2:12 or greater) (complete a thru k)

- a. Tile manufacturer and product name:

- b. Certified Test Report/Product Approval number:

- c. Installed systems from Certified Test Report/Product Approval:
Product approvals may include installation information for different systems. Enter design pressure rating for each installed system as applicable (enter up to 3):
 Installed System 1:
 System number: _____ design pressure or moment resistance rating of installed system 1: _____
 Installed System 2: (if applicable)
 System number: _____ design pressure or moment resistance rating of installed system 2: _____
 Installed System 3: (if applicable)
 System number: _____ design pressure or moment resistance rating of installed system 3: _____
- d. Check here to confirm that the design pressure rating/moment resistance of installed system(s) is adequate for the site conditions and required design uplift pressures in section 4.
- e. Tile impact rating (Select one of the following):
 - FM 4473 Class 4 (required for FORTIFIED Hail Supplement)
 - No impact rating, cannot be verified, or other
- f. Structural Supports Certified Test Report/Product Approval Number:

- g. Mechanical roof tile attachment:
 Fastener type: _____
 Fastener's size: _____



RCF3 - Roofing Compliance Form for Tile Roof Cover – New Roof or Re-Roof

Fastener quantity (per tile): _____

Do tile fasteners meet FORTIFIED Corrosion Resistance Requirements per Standard Detail [F-G-1](#)? Yes No

h. Adhesive foam attachment:

Check here to confirm that foam installer is certified by manufacturer (certification number required in section 15)

Adhesive foam product name and manufacturer:

Adhesive Certified Test Report/Product Approval Number:

i. Tile underlayment Certified Test Report/Product Approval Number:

j. Check here to confirm that the required design pressure reports listed in section 4.7.2 of the *FORTIFIED Home 2020 Standard* for installed tile system and adhesives have been provided to FORTIFIED Evaluator.

k. Check here to confirm that tile (including hip and ridge tile) and metal flashing are installed in accordance with manufacturer installation instructions and FRSA/TRI *Florida High Wind Concrete and Clay Tile installation Manual* (5th Edition for ASCE 7-10 or 6th Edition for ASCE 7-16).

10. Hurricane Designation Only: Roof Mounted Attic Vents (complete a OR b OR c)

a. Check here if attic is sealed (i.e., no ventilation at soffits, gable end vents, or attic vents of any kind)

b. Check here if attic is not sealed, and there are NO roof-mounted vents installed

c. Enter type and rating of installed roof-mounted vents

Ridge vents manufacturer and model _____

Off-ridge vents manufacturer and model _____

Turbines manufacturer and model _____

Check here if all roof-mounted vents meet requirements of Florida Building Code TAS 100 (A) (required)

Check here to confirm that all roof-mounted vents are installed per the vent manufacturer's high wind installation requirements.

11. Photovoltaic (PV) panels (complete a and b OR c)

a. Check here to confirm that PV panels were installed and anchored to the roof to resist site design wind loads in accordance with engineered anchorage details.

b. Impact rating (Select all that apply):

Flexible PV modules that are FM Approved for hail or meet FM 4476 that includes a Severe Hail rating (*acceptable for FORTIFIED Hail Supplement*)

Rigid PV modules that are FM Approved for hail or meet FM 4478 that includes a Class 4 rating (*acceptable for FORTIFIED Hail Supplement*)

Rigid modules that meet UL 1703 Standards for Flat-Plate Photovoltaic Modules and Panels (*acceptable for FORTIFIED Hail Supplement*)

Other impact rating, cannot be verified, or no rating

c. Check here if there are no PV panels installed on the roof



RCF3 - Roofing Compliance Form for Tile Roof Cover – New Roof or Re-Roof

12. Skylights (complete a and b OR c OR d)

- a. Impact rating (Select all that apply):
 - ASTM E1886 with ASTM E1996 rated “B,” “C,” “D,” or “E” (acceptable for FORTIFIED Hail Supplement)
 - ANSI/FM 4431 with Severe Hail Rating (acceptable for FORTIFIED Hail Supplement)
 - Current Miami-Dade County NOA (acceptable for FORTIFIED Hail Supplement)
 - other impact rating, cannot be verified or no rating
- b. Check here to confirm that skylights and light tunnels have been installed per manufacturer’s installation instructions for high-wind and/or to meet applicable design pressures ratings.
- c. Check here if there are no skylights installed on the roof
- d. For re-roofing applications only, check here if skylight is existing and skylight ratings and installation are unknown

13. Confirmation of Completion

I certify that I am the Installing Roofing Contractor Responsible Party licensed or authorized in the state of _____ and that the above information is true and accurate as of the date shown below. I understand that false or fraudulent information with the intent to deceive will be reported under insurance fraud guidelines.

Signature: _____ Date: _____

Printed Name: _____

Company: _____

Phone Number: _____

Address: _____

City: _____

State: _____ ZIP: _____

License or Registration Number: _____

FORTIFIED Wise Roofing Contractor ID Number: _____

TRI certification Number: _____

Foam Installer Manufacturer Certification Number: _____